



Household/Craft

Queen Resin

Technical data sheet
n° 738 Rev. 28/04/2014

Category:

- Special waxes

Applications:

- Highly footfall resistant waxing

Advantages:

- Self-polishing
- Double reticulation
- Very high resistance

Product for professional use. The manufacturer declines all responsibility for any damage caused by an improper use of the product.

Highly resistant self-polishing sealing wax specific for resin floors

Applications

Queen Resin is a self-polishing sealing wax with double reticulation (acrylic-urethane) specific for resin floors.

Queen Resin creates a very long lasting glossy film on treated floors, very resistant to footfall and also to the traffic of trolleys and forklifts.

The floor becomes very shiny and resistant to dust, dirt, black heels marks etc., allowing maintenance to be reduced to a minimum.

Fields of application

Queen Resin is ideal for highly walkable areas such as shops, stores, schools, hospitals, offices, business premises, etc.

It can also be used as a surface finish on wood, earthenware, pre-sealed cement.

Method of Use

The surfaces must be clean and compact. Wash the floor thoroughly to remove any dust, grease, oil and dirt in general. Rinse and let it dry. Apply Queen Resin evenly with a brush, roller or wax spreader. After about an hour, apply a second coat crosswise to the first.

If you want to increase the degree of gloss further, apply a third coat.

The consumption of Queen Resin is about 30-50 g/m² per coat depending on the surface porosity.

Avoid pouring Queen Resin directly on the floor or leaving the rag soaked in the product on the tiles for a long time, as it could leave stains.