

MORPEL/A

Technical Sheet n° 255 Rev. 18/06/2015

Softener for leather processing

APPLICATIONS:

Morpel/A is a softener for leather, both natural and synthetic, that makes processing easier and allows to avoid tearing and cracks. It can be also used for uppers and finished footwear, for shaping for example. It is particularly appropriate for leathers that are damaged by pre-treatments and tanning processes or before complicated processes such as pre-assembling and uppers' crimping. After use, the product evaporates fast, leaving surfaces dry and immediately workable. Thanks to Morpel/A the average amount of production wastes diminishes considerably.

METHOD OF USE:

Morpel/A can be used both raw or diluted with water at the maximum proportion of 1:1. It can be distributed with a brush or sprayed, in case of wide surfaces, or by means of a sprinkler pump (for boilers for instance). With cambering and pre-assembling machines, whole leathers, use it diluted with water at 1:1, spraying abundantly before processing. After evaporation or immediately after having distributed it, proceed with normal shaping, sewing and assembly operations.

FIELD OF APPLICATION

- Unique product
- Easy to use
- Compatible with all machines' components (steel, aluminium and various alloys)

TECHNICAL CHARACTERISTICS

Aspect	Liquid
Colour	White
Smell	Characteristic
pH	9,5
Density (20°C)	0,985 g/c m3