

# RESIN COTTO

Technical data sheet n° 194 Rev. 30/03/2015

Waterproofing agent for earthenware and stoneware floors

## APPLICATIONS:

Resin Cotto is an indoor floor sealant with excellent water repellence and good abrasion resistance. Resin Cotto prevents the absorption of dirt of various kinds such as dust, oil, grease and liquids in general. Its use enhances the aesthetic qualities of floorings and surfaces consisting of stoneware, earthenware and solid bricks. The product can also be used as anti-dust for cement surfaces and for mortars employed for laying bricks. In the treatment of freshly laid outdoor flooring, or where there is a rising damp, we recommend using the product Aura.

## METHOD OF USE:

The floor must be cleaned and dried. If necessary, degrease thoroughly the floor thoroughly with the product Alcott, in the case there are traces of oily dirt, or with the acid cleaner Mogol 500b. to remove any dust, grease, oil and dirt in general. Rinse well and let it dry. Apply Resin Cotto preferably with a roller or a brush, being careful to apply it horizontally, and after it has dried, applying a second coat vertically. Avoid pouring the product directly on the floor or leaving rollers, brushes or rags on the surfaces, as they could leave stains and halos, which are very difficult to remove.

DRYING (At a temperature of 20°C):

Dry: 2/3 hours

Dry in depth: 3/4 days

Indicative consumption per litre of product: variable depending on the absorption of the supports, from 5 to 6 square metres for very porous materials, up to 18/20 for low-absorbent materials.

## CATEGORY:

- Cleaner for marble and natural stone

## ADVANTAGES:

- Neutral
- No need to rinse
- No foam