

SILIPAV ECO/C

Technical data sheet n° 676 Rev. 28/04/2014

Silicone wet-look ecological protective impregnating agent for stones, earthenware, bricks and wood

APPLICATIONS:

Silipav Eco/C is an aqueous formulation based on special silicone emulsions, created to protect and waterproof surfaces in:

- Earthenware • Natural stones • Untreated wood

Silipav Eco/C penetrates deep into the porosity of the material to be treated, creating a waterproof barrier that prevents the absorption of water and dirt. The product also gives a pleasant “wet-look” to the treated surfaces. Silipav Eco/C is resistant to U.V rays (it does not turn yellow) and to washing with common household detergents. Being water based, the product is absolutely odourless and free of hazardousness.

METHOD OF USE:

The surface to be treated must be clean, dry and in any case free from any sealing treatments (resins or waxes). Dilute the product to 25% in water (for example, make up 250 ml to one litre with water). Pour the product directly onto the surface and distribute it with a roller or a brush. Allow the product to absorb for at least 15 minutes, and then remove any excess with a soft cloth. One hand is usually sufficient. Any second coat must be applied before the complete drying of the first coat (wet-on-wet). The treated surface is walkable after 12/24h (depending on the temperature) and the treatment reaches its maximum effectiveness after 7 days. **ATTENTION** The product contains a silicone emulsion and can prevent the adhesion of paints and similar. Therefore, avoid treating surfaces that should be painted later. **YIELD:** The amount of product required is between 3 and 10 m²/litre of diluted product, depending on the porosity of the material to be treated.

CATEGORY:

- Wet-look protective waterproof agent

ADVANTAGES:

- Ecological
- Concentrated
- High yield