

SVERNISOLV GEL L

Technical Sheet n° 682 Rev. 01/07/2014

Industrial paint stripper

APPLICATIONS:

Svernisolv Gel/L removes easily, and at room temperature, solvent, powder and water paints.

The product is effective against synthetic, epoxy, polyurethane, polyvinyl resins, etc.; it does not contain toxic or harmful by inhalation solvents (such as methylene chloride, phenols, methanol and formic acid) and has a very limited odour.

The gel formulation makes it suitable also for on-the-spot applications on vertical walls or on large pieces that cannot be immersed in the paint removal tanks.

It is non-flammable and is removed by simple washing with water.

It can be used on metals, wood and industrial plastics.

If used on aluminium, brass or zamak, do not rinse the product with water, in order not to cause corrosion.

METHOD OF USE:

Use it as it is. Spread the product by brush or other means on the surface to be treated, wait for the time necessary to remove the paint (variable depending on the type) and then remove the gel with water. For the components in aluminium, light alloys, brass and zamak, remove with a cloth or other means.

It is advisable to try the product on a small surface to check its compatibility with the support to be treated.

STRENGTHS:

- Highly efficient
- All-purpose product

TECHNICAL CHARACTERISTICS

Aspect	Gel
Odor	Characteristic
Colour	Light
Density (20°C)	0.982 g/cm ³

Certified Quality System UNI EN ISO 9001

PAGE 01